



PARAFFIN ATF DEXRON III

The Right Choice in Lubricants

PARAFFIN AUTOMATIC TRANSMISSION FLUID DEXRON III is an extra high performance automatic transmission oil, formulated with high quality hydro-treated base stocks, shear stable viscosity index improvers and advanced additive system to meet or exceed the latest requirements of Ford Mercon and General Motors for Dexron III specification. Suitable for passenger cars and commercial automatic transmissions, for use in applications like power steering systems, hydraulics and some manual transmissions where automatic transmission fluid is specified.

FEATURES AND BENEFITS

- Vibration free and very smooth gear shifting
- Outstanding oxidation stability for cleaner automatic transmission systems
- Extended fluid life with robust anti-wear protection for longer transmission component life

APPLICATION

Recommended for all vehicles of Ford requiring MERCON® quality fluids and General Motors requiring DEXRON®-III quality fluids.

TYPICAL TECHNICAL PROPERTIES

TEST PARAMETERS	TEST METHOD	TYPICAL VALUE
VISCOSITY @ 100 °C, cSt	ASTM D445	7.1
VISCOSITY @ 40 °C, cSt	ASTM D445	33
POUR POINT, °C	ASTM D97	-42°C
VISCOSITY INDEX	ASTM D2270	186
FOAM TEST, ml Seq. I	ASTM D892	10/0
Seq. II	ASTM D892	10/0
Seq. III	ASTM D892	0/0
FLASH POINT, (C.O.C.)	ASTM D92	220°C
Density @15°C kg/l	ASTM D-1298	0.845
Brookfield Viscosity @-40°C cp	ASTM 2983	15600



📍 Al Ghail Industrial Park - Ras Al Khaimah - United Arab Emirates

☎ +971 7 266 7906 📞 +971 50 327 2769 📧 📱

✉ sales@paraffinlubricants.com 🌐 www.paraffinlubricants.com

📘 paraffinoilrefineryandmanufacturing 📺 paraffinoilmanufacturing

Packaging Sizes: 1L 3L 4L 5L 20L 25L 208L